





TOB 111 (LRV = 63)



TOB 115 (LRV = 54)



TOB 123 (LRV = 14)



TOB 114 (LRV = 44)



TOB 120 (LRV = 10)



TOB 113 (LRV = 30)



TOB 110 (LRV = 35)



TOB 119 (LRV = 32)



TOB 122 (LRV = 22)



TOB 117 (LRV = 9)



TOB 118 (LRV = 12)



TOB 121 (LRV = 12)



TOB 116 (LRV = 76)



TOB 107 (LRV = 67)



TOB 112 (LRV = 71)



TOB 108 (LRV = 76)



TOB 106 (LRV = 53)



TOB 105 (LRV = 28)



TOB 124 (LRV = 26)



TOB 104 (LRV = 70)



TOB 102 (LRV = 27)



TOB 109 (LRV = 16)



TOB 103 (LRV = 32)



TOB 101 (LRV = 11)

TECHNICAL INFORMATION



Physical Properties:

Total Weight: 460g/m² (nominal)

Vinyl Weight: 400g/m² (nominal)

Substrate Type: Woven Polyester
Cotton Scrim



Substrate Weight: 60g/m² (nominal)

Other specifications available

Tensile Strength: MD 80 N/cm (nominal)

TD 60 N/cm (nominal)

Tear Strength: 8500 mN (nominal)



Roll Size:

130cm x 30m – cut lengths available



Pattern Repeat:

Vertical: Free match

Horizontal: 1300mm



Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS476 Part 7). Euroclass B-s1,d0. Class A ASTM E-84 Tunnel Test.



Adhesive:

Fabric backed vinyls – Newmor Heavy. Varies with substrate – please enquire.



Bacteria Resistance:

Contains an active fungicide.



Light Fast:

Excellent Light Fastness

BS EN ISO 105-B02 7/8.

LRV = Light Reflective Value

Specifications:

Conforms to requirements of BS EN 15102, BS EN 259 and WA – Quality Standard W-101.

Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test.

Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

Our management systems and production procedures comply with ISO 9001, the internationally recognised Quality Standard.

Availability:

Every product stocked in depth. 5.00pm deadline for next day delivery. (UK only)

Origin:

Designed, coloured, manufactured and stocked in the UK.

Warranty:

Newmor offers a five year warranty against manufacturing defects. Full details available on application.

Samples:

Larger samples are readily available on request.

Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Most products are also able to withstand the use of chlorine releasing agent solutions.

Customise this design



youchoose[™]

Our Unique Re-Colouration Service

www.newmor.com



BCFA
member



British Product (Global Support)

www.newmor.com

PREMIER COLLECTION